NSN 4140-00-535-4626

Centrifugal Fan - Page 1 of 2

Speed Adjustments:

Single speed

13.875 inches

Width:

Length:



View Online at https://aerobasegroup.com/nsn/4140-00-535-4626

| Ambient Tempurature At Full Rated Power: |
|---|
| / mbione romparataro / ter an reatou r o non |
| -54.0 degrees celsius and 85.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 3450.0 |
| Electrical Connection Type: |
| Terminal block |
| Outlet Inside Width: |
| 4.969 inches |
| Outlet Inside Height: |
| 2.125 inches |
| Static Pressure At Specificationified Air Flow Rate: |
| 2.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Partially enclosed |
| • |
| Mounting Facility Type And Quantity: |
| |
| Mounting Facility Type And Quantity: |
| Mounting Facility Type And Quantity: 4 unthreaded hole |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower Prime Mover Drive Shaft Bearing Type: |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower Prime Mover Drive Shaft Bearing Type: Ball |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Horizontal |

NSN 4140-00-535-4626Centrifugal Fan - Page 2 of 2



| Frequency In Hertz: |
|---|
| 60.0 |
| Height: |
| 8.625 inches |
| Material: |
| Steel housing |
| Surface Treatment: |
| Primer housing outside and enamel housing outside |
| Style Designator: |
| Fixed, rectangular outlets |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A087a0 |