NSN 4140-00-535-4626

Centrifugal Fan - Page 1 of 2

Speed Adjustments:

Single speed

13.875 inches

Width:

Length:



View Online at https://aerobasegroup.com/nsn/4140-00-535-4626

Ambient Tempurature At Full Rated Power:
/ mbione romparataro / ter an reatou r o non
-54.0 degrees celsius and 85.0 degrees celsius
Operating Speed At Rated Capacity In Rpm:
3450.0
Electrical Connection Type:
Terminal block
Outlet Inside Width:
4.969 inches
Outlet Inside Height:
2.125 inches
Static Pressure At Specificationified Air Flow Rate:
2.0 inches of water
Drive Type:
Direct
Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
•
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 unthreaded hole
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed:
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate:
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location:
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type:
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating:
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower Prime Mover Drive Shaft Bearing Type:
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower Prime Mover Drive Shaft Bearing Type: Ball
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction:
Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 480.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 208.0 ac or 440.0 ac Prime Mover Power Rating: 0.750 horsepower Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Horizontal

NSN 4140-00-535-4626Centrifugal Fan - Page 2 of 2



Frequency In Hertz:
60.0
Height:
8.625 inches
Material:
Steel housing
Surface Treatment:
Primer housing outside and enamel housing outside
Style Designator:
Fixed, rectangular outlets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A087a0