

View Online at <https://aerobasegroup.com/nsn/4140-00-535-4627>

**Diameter:**

6.200 inches

**Environmental Protection:**

Splash proof

**Ambient Temperature At Full Rated Power:**

85.0 degrees celsius and 139.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3350.0

**Outlet Inside Width:**

4.969 inches

**Outlet Inside Height:**

2.125 inches

**Static Pressure At Specificationified Air Flow Rate:**

3.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

1 clamp

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

425.000 cubic feet per minute

**Voltage In Volts And Current Type:**

208.0 ac or 440.0 ac

**Prime Mover Power Rating:**

0.750 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Three

**Material:**

Steel

**Surface Treatment:**

Primer housing outside and enamel housing outside

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0