

View Online at <https://aerobasegroup.com/nsn/4140-00-540-1109>

**Speed Adjustments:**

Single speed

**Diameter:**

2.000 inches

**Length:**

3.375 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Fungus resistant and salt spray resistant

**Ambient Temperature At Full Rated Power:**

-65.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

13500.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

24.000 cubic feet per minute

**Voltage In Volts And Current Type:**

24.0 dc or 29.0 dc

**Prime Mover Power Rating:**

0.003 horsepower

**Housing Inside Diameter:**

2.125 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Special Features:**

2.25 in. Sq flange w/hole ea corner at intake end of venturi tube

**Material:**

Aluminum alloy

**Quantity:**

1

**Surface Treatment:**

Enamel blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0