

View Online at <https://aerobasegroup.com/nsn/4140-00-540-6731>

**Speed Adjustments:**

Single speed

**Width:**

1.000 inches

**Length:**

1.000 inches

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 110.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

21500.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

3 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

2.200 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

6.3 ac

**Prime Mover Power Rating:**

0.004 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Two or single

**Material:**

Aluminum housing

**Surface Treatment:**

Anodize housing outside

**Style Designator:**

Fixed, multistage

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0