

View Online at <https://aerobasegroup.com/nsn/4140-00-540-6731>

Speed Adjustments:

Single speed

Width:

1.000 inches

Length:

1.000 inches

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 110.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

21500.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

3 threaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

2.200 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

6.3 ac

Prime Mover Power Rating:

0.004 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Phase:

Two or single

Material:

Aluminum housing

Surface Treatment:

Anodize housing outside

Style Designator:

Fixed, multistage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0