

View Online at <https://aerobasegroup.com/nsn/4140-00-554-8143>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

17.500 inches

**Length:**

27.125 inches

**Flow Direction:**

Outward

**Operating Speed At Rated Capacity In Rpm:**

3450.0

**End Application:**

W/s: fans; forrestal class cv; nimitz class cvn; kidd class ddg; wasp class lhd; tarawa class lha; emory s. Land class as; supply class aoe; fms-knox class ff; fms-newport classlst

**Electrical Connection Type:**

Terminal block

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise

**Voltage In Volts And Current Type:**

440.0 ac

**Prime Mover Power Rating:**

5.000 horsepower

**Housing Inside Diameter:**

18.000 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Material:**

Aluminum alloy housing

**Material Specification:**

Qq-a-250/11 federal specification single material response housing

**Quantity:**

1

**Style Designator:**

Fixed

**Test Data Document:**

81349-milf18953 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0