

View Online at <https://aerobasegroup.com/nsn/4140-00-555-1302>

Stage Quantity:

1

Diameter:

2.875 inches

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

23300.0

Static Pressure At Specificationified Air Flow Rate:

6.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Nonsparking

Air Flow Rate:

75.000 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.125 horsepower

Housing Inside Diameter:

2.875 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum housing

Quantity:

1

Surface Treatment:

Anodize housing inside and paint housing inside

Style Designator:

Fixed

Fsc Application Data:

Rack assembly, aft escape hatch electronic, equipment, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A087a0