

View Online at <https://aerobasegroup.com/nsn/4140-00-555-1776>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

12.500 inches

Length:

19.375 inches

Flow Direction:

Outward

Environmental Protection:

Splash proof

Ambient Temperature At Full Rated Power:

50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3450.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

3.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 bracket

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

1575.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

1.250 horsepower

Housing Inside Diameter:

12.688 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

60.0

Material:

Steel housing

Material Specification:

Qq-s-698 federal specification single material response housing

Quantity:

1

Surface Treatment:

Zinc housing outside

Style Designator:

Fixed

Reference Number Differentiating Characteristics:

As differentiated by ajlg and csbh

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0