

View Online at <https://aerobasegroup.com/nsn/4140-00-555-1776>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

12.500 inches

**Length:**

19.375 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Splash proof

**Ambient Temperature At Full Rated Power:**

50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3450.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

3.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 bracket

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

1575.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

1.250 horsepower

**Housing Inside Diameter:**

12.688 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Material:**

Steel housing

**Material Specification:**

Qq-s-698 federal specification single material response housing

**Quantity:**

1

**Surface Treatment:**

Zinc housing outside

**Style Designator:**

Fixed

**Reference Number Differentiating Characteristics:**

As differentiated by ajlg and csbh

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0