

View Online at <https://aerobasegroup.com/nsn/4140-00-564-5980>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

4.016 inches

Environmental Protection:

Dustproof and explosion proof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

8000.0

End Application:

Sircraft, phantom f-4; aircraft, hercules c-130; simulator, c-130; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); helicopter, uh-60a/uh-60d

Electrical Connection Type:

Connector

Outlet Inside Width:

0.875 inches

Outlet Inside Height:

1.188 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

10.9 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

27.0 dc

Prime Mover Power Rating:

0.012 horsepower

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Special Features:

Positioning when mtg determines discharge blast direction, part number 19a513 is not coated

Material:

Plastic phenolic housing

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0