

View Online at <https://aerobasegroup.com/nsn/4140-00-585-8366>

**Speed Adjustments:**

Single speed

**Length:**

2.625 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Corrosion resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-18.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3200.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

80.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.003 horsepower

**Housing Inside Diameter:**

4.594 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Material:**

Aluminum

**Surface Treatment:**

Anodize blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0