NSN 4140-00-586-7604

Centrifugal Fan - Page 1 of 2

Stage Quantity:



View Online at https://aerobasegroup.com/nsn/4140-00-586-7604

Speed Adjustments:
Single speed
Width:
8.718 inches
Diameter:
4.500 inches
Length:
7.810 inches
Operating Speed At Rated Capacity In Rpm:
5400.0
End Application:
An/mps-t1
Electrical Connection Type:
Wire lead
Outlet Inside Width:
3.000 inches
Outlet Inside Height:
3.190 inches
Static Pressure At Specificationified Air Flow Rate:
0.0 inches of water
Drive Type:
Drive Type.
Direct
Direct
Direct Prime Mover Type:
Direct Prime Mover Type: Electric motor
Direct Prime Mover Type: Electric motor Inclosure Type:
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity:
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed:
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed: Clockwise
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed: Clockwise Air Flow Rate:
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed: Clockwise Air Flow Rate: 485.0 cubic feet per minute
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed: Clockwise Air Flow Rate: 485.0 cubic feet per minute Outlet Location:
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed: Clockwise Air Flow Rate: 485.0 cubic feet per minute Outlet Location: Top
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed: Clockwise Air Flow Rate: 485.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type:
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed: Clockwise Air Flow Rate: 485.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 200.0 ac
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 clamp Rotation Direction For Which Designed: Clockwise Air Flow Rate: 485.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 200.0 ac Prime Mover Drive Shaft Bearing Type:

NSN 4140-00-586-7604

Centrifugal Fan - Page 2 of 2



Phase:
Three
Height:
8.720 inches
Material:
Steel housing
Quantity:
1
Surface Treatment:
Zinc housing outside and enamel housing outside
Style Designator:
Fixed, rectangular outlets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A087a0