NSN 4140-00-601-4013

Centrifugal Fan - Page 1 of 2

Speed Adjustments:

Single speed

8.380 inches **Length:**

Width:



View Online at https://aerobasegroup.com/nsn/4140-00-601-4013

6.310 inches
Ambient Tempurature At Full Rated Power:
85.0 degrees celsius
Operating Speed At Rated Capacity In Rpm:
3000.0
Electrical Connection Type:
Wire lead
Outlet Inside Width:
2.500 inches
Outlet Inside Height:
4.140 inches
Static Pressure At Specificationified Air Flow Rate:
0.0 inches of water
Drive Type:
Direct
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Mounting Facility Type And Quantity:
mounting ruenity Type And Quantity.
4 threaded hole
4 threaded hole
4 threaded hole Rotation Direction For Which Designed:
4 threaded hole Rotation Direction For Which Designed: Counterclockwise
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate:
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location:
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type:
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating:
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 0.010 horsepower
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 0.010 horsepower Prime Mover Drive Shaft Bearing Type:
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 0.010 horsepower Prime Mover Drive Shaft Bearing Type: Ball
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 0.010 horsepower Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction:
4 threaded hole Rotation Direction For Which Designed: Counterclockwise Air Flow Rate: 230.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 0.010 horsepower Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Horizontal

NSN 4140-00-601-4013Centrifugal Fan - Page 2 of 2



Special Features:
Flanged outlet
Frequency In Hertz:
60.0
Height:
7.370 inches
Material:
Steel
Surface Treatment:
Cadmium blade
Style Designator:
Fixed, rectangular outlets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A087a0