

View Online at <https://aerobasegroup.com/nsn/4140-00-609-9258>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

7.000 inches

Length:

9.375 inches

Flow Direction:

Outward

Environmental Protection:

Moisture resistant

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5600.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

3.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

6 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking and safety impeller guard

Air Flow Rate:

245.000 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.250 horsepower

Housing Inside Diameter:

7.030 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Material Specification:

Qq-a-596 comp b federal specification single material response

Quantity:

1

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-7720, type iii military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-7720 spec.