

View Online at <https://aerobasegroup.com/nsn/4140-00-618-5389>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

4.469 inches

**Length:**

6.375 inches

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Operating Speed At Rated Capacity In Rpm:**

3300.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

0.938 inches

**Outlet Inside Height:**

2.312 inches

**Static Pressure At Specificationified Air Flow Rate:**

1.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded insert

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

30.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.048 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Three

**Height:**

6.031 inches

**Material:**

Steel

**Surface Treatment:**

Cadmium blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0