

View Online at <https://aerobasegroup.com/nsn/4140-00-618-7010>

**Speed Adjustments:**

Single speed

**Width:**

9.719 inches

**Length:**

7.812 inches

**Environmental Protection:**

Corrosion resistant and fungus proof and moisture resistant

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2830.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

4.750 inches

**Outlet Inside Height:**

Between 3.120 inches and 3.130 inches

**Static Pressure At Specificationified Air Flow Rate:**

1.9 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

440.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.442 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Height:**

8.719 inches

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0