NSN 4140-00-620-5765

Centrifugal Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-620-5765

Speed Adjustments:
Single speed
Width:
4.406 inches
Length:
3.500 inches
Environmental Protection:
Fungus resistant and humidity proof and vibration proof
Ambient Tempurature At Full Rated Power:
-55.0 degrees celsius and 85.0 degrees celsius
Operating Speed At Rated Capacity In Rpm:
8000.0
Electrical Connection Type:
Cord w/attached plug
Outlet Inside Width:
1.030 inches
Outlet Inside Height:
1.343 inches
Static Pressure At Specificationified Air Flow Rate:
1.8 inches of water
Drive Type:
Direct
Prime Mover Type:
Prime Mover Type: Electric motor
Electric motor
Electric motor Inclosure Type:
Electric motor Inclosure Type: Fully enclosed
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 34.000 cubic feet per minute
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 34.000 cubic feet per minute Outlet Location:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 34.000 cubic feet per minute Outlet Location: Bottom
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 34.000 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 34.000 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 34.000 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 34.000 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 0.025 horsepower
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 3 threaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 34.000 cubic feet per minute Outlet Location: Bottom Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 0.025 horsepower Prime Mover Drive Shaft Bearing Type:

NSN 4140-00-620-5765

Centrifugal Fan - Page 2 of 2



Phase:
Single
Frequency In Hertz:
400.0
Height:
3.250 inches
Material:
Aluminum
Surface Treatment:
Anodize
Style Designator:
Fixed, rectangular outlets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A087a0