

View Online at <https://aerobasegroup.com/nsn/4140-00-621-2271>

Stage Quantity:

1

Speed Adjustments:

Two speed

Width:

5.438 inches

Diameter:

1.160 inches

Length:

2.953 inches

Environmental Protection:

Humidity proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

10300.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

0.838 inches

Outlet Inside Height:

1.203 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

45.0 cubic feet per minute

Outlet Location:

Bottom

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.020 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Phase:

Single

Special Features:

Operates 8900.0 rpm at 1000 cps and 10000.0 rpm at 380 cps

Height:

3.515 inches

Material:

Steel

Quantity:

2

Surface Treatment:

Cadmium blade

Style Designator:

Fixed, dual impeller, rectangular outlet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0