

View Online at <https://aerobasegroup.com/nsn/4140-00-621-2271>

**Stage Quantity:**

1

**Speed Adjustments:**

Two speed

**Width:**

5.438 inches

**Diameter:**

1.160 inches

**Length:**

2.953 inches

**Environmental Protection:**

Humidity proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 71.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

10300.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

0.838 inches

**Outlet Inside Height:**

1.203 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

45.0 cubic feet per minute

**Outlet Location:**

Bottom

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.020 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Single

**Special Features:**

Operates 8900.0 rpm at 1000 cps and 10000.0 rpm at 380 cps

**Height:**

3.515 inches

**Material:**

Steel

**Quantity:**

2

**Surface Treatment:**

Cadmium blade

**Style Designator:**

Fixed, dual impeller, rectangular outlet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0