

View Online at <https://aerobasegroup.com/nsn/4140-00-624-1240>

**Stage Quantity:**

1

**Environmental Protection:**

Splash proof

**Ambient Temperature At Full Rated Power:**

55.0 degrees celsius and 71.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3200.0

**Outlet Inside Width:**

0.938 inches

**Outlet Inside Height:**

3.688 inches

**Static Pressure At Specificationified Air Flow Rate:**

1.4 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

118.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.100 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Single

**Material:**

Steel

**Quantity:**

1

**Surface Treatment:**

Enamel housing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0