

View Online at <https://aerobasegroup.com/nsn/4140-00-627-2556>

Speed Adjustments:

Single speed

Length:

2.500 inches

Flow Direction:

Outward

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-6.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3800.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 clamp and 2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

325.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.043 horsepower

Housing Inside Diameter:

6.858 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Synclamp p/h 501035; rubber nipple p/n 476608

Frequency In Hertz:

400.0

Material:

Plastic polycarbonate blade

Quantity:

1

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0