

View Online at <https://aerobasegroup.com/nsn/4140-00-640-5778>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

4.625 inches

Length:

4.625 inches

Environmental Protection:

Fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-29.0 degrees celsius and 148.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3000.0

Electrical Connection Type:

Wire lead

Outlet Inside Height:

1.875 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Nonsparking

Air Flow Rate:

60.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.033 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Phase:

Single

Height:

4.812 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, rectangular outlets

Fsc Application Data:

Training set radar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0