

View Online at <https://aerobasegroup.com/nsn/4140-00-640-5807>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

16.062 inches

Diameter:

4.500 inches

Length:

7.810 inches

Environmental Protection:

Salt spray resistant

Ambient Temperature At Full Rated Power:

-18.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3200.0

Electrical Connection Type:

Terminal block

Outlet Inside Width:

3.188 inches

Outlet Inside Height:

4.063 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 2 threaded hole

Rotation Direction For Which Designed:

Clockwise and counterclockwise

Air Flow Rate:

880.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

220.0 ac

Prime Mover Power Rating:

0.830 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Three

Height:

8.720 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, dual impeller, rectangular outlet

Test Data Document:

18876-9155592 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0