

View Online at <https://aerobasegroup.com/nsn/4140-00-640-6809>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

10.125 inches

Length:

6.375 inches

Environmental Protection:

Shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-65.0 degrees fahrenheit and 205.0 degrees fahrenheit

Operating Speed At Rated Capacity In Rpm:

3208.0

Electrical Connection Type:

Wire lead

Outlet Inside Height:

1.750 inches

Static Pressure At Specificationified Air Flow Rate:

3.0 inches of water

Drive Type:

Gear

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

4 feet and 16 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

50.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Single

Special Features:

Ratio of motor shaft gear to centrifugal impeller shaft gear produces 775 rpm for impeller; motor shaft extended at other end and fitted w/4 in. Diameter propeller type fan blade; w/wire guard; ccw rotation facing air discharge; air flow over motor and through blades; w/centrifugal switch and lead for control of interlock accessory

Height:

5.607 inches

Material:

Aluminum

Surface Treatment:

Anodize

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0