

View Online at <https://aerobasegroup.com/nsn/4140-00-683-8477>

Speed Adjustments:

Single speed

Length:

1.563 inches

Flow Direction:

Outward

Environmental Protection:

Explosion proof and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

19000.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

3 threaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

60.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.061 horsepower

Housing Inside Diameter:

1.890 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0