

View Online at <https://aerobasegroup.com/nsn/4140-00-683-8802>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

4.280 inches

**Length:**

5.360 inches

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

10200.0

**Electrical Connection Type:**

Terminal block

**Outlet Inside Width:**

0.750 inches

**Outlet Inside Height:**

1.250 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 8 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

46.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Power Rating:**

0.117 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Three

**Height:**

5.000 inches

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, rectangular outlets

**Test Data Document:**

10001-2515297-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0