NSN 4140-00-684-3897

Centrifugal Fan - Page 1 of 2

Stage Quantity:



View Online at https://aerobasegroup.com/nsn/4140-00-684-3897

Speed Adjustments:
Single speed
Width:
9.844 inches
Diameter:
5.000 inches
Length:
12.000 inches
Ambient Tempurature At Full Rated Power:
-28.0 degrees celsius and 65.0 degrees celsius
Operating Speed At Rated Capacity In Rpm:
3330.0
Electrical Connection Type:
Terminal block
Outlet Inside Width:
3.812 inches
Outlet Inside Height:
4.938 inches
Static Pressure At Specificationified Air Flow Rate:
0.0 inches of water
Drive Type:
Direct
Prime Mover Type:
rillie mover Type.
Electric motor
Electric motor
Electric motor Inclosure Type:
Electric motor Inclosure Type: Fully enclosed
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed:
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided:
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided: Safety impeller guard
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided: Safety impeller guard Air Flow Rate:
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided: Safety impeller guard Air Flow Rate: 750.0 cubic feet per minute
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided: Safety impeller guard Air Flow Rate: 750.0 cubic feet per minute Outlet Location:
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided: Safety impeller guard Air Flow Rate: 750.0 cubic feet per minute Outlet Location: Bottom or top
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided: Safety impeller guard Air Flow Rate: 750.0 cubic feet per minute Outlet Location: Bottom or top Voltage In Volts And Current Type:
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided: Safety impeller guard Air Flow Rate: 750.0 cubic feet per minute Outlet Location: Bottom or top Voltage In Volts And Current Type: 440.0 ac
Electric motor Inclosure Type: Fully enclosed Rotation Direction For Which Designed: Clockwise Features Provided: Safety impeller guard Air Flow Rate: 750.0 cubic feet per minute Outlet Location: Bottom or top Voltage In Volts And Current Type: 440.0 ac Prime Mover Power Rating:

NSN 4140-00-684-3897

Centrifugal Fan - Page 2 of 2

Fiig: A087a0



Discharge Direction:
Angular down and angular up and horizontal and vertical down and vertical up
Phase:
Three
Height:
9.156 inches
Material:
Steel
Surface Treatment:
Cadmium blade
Style Designator:
Fixed, rectangular outlets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No