

View Online at <https://aerobasegroup.com/nsn/4140-00-684-7213>

Speed Adjustments:

Single speed

Width:

10.781 inches

Length:

9.125 inches

Environmental Protection:

Fungus proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-40.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3800.0

Electrical Connection Type:

Terminal box

Outlet Inside Width:

3.719 inches

Outlet Inside Height:

3.812 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 base plate and 4 threaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

550.0 cubic feet per minute

Outlet Location:

Bottom

Voltage In Volts And Current Type:

200.0 ac or 230.0 ac

Prime Mover Power Rating:

0.840 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Phase:

Three

Special Features:

Duct clamp type outlet, four mtg holes 3/8-24 unf2b, 1/2 in. Deep in mtg surface of motor base on 1-5/8 in. By 3-1/8 mtg centers

Frequency In Hertz:

400.0

Height:

9.844 inches

Material:

Steel

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0