

View Online at <https://aerobasegroup.com/nsn/4140-00-701-0309>

Speed Adjustments:

Single speed

Length:

1.734 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3350.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.2 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

57.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.038 horsepower

Housing Inside Diameter:

3.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

W/rim at ea end of venturi tube for clamp mtg, air flow reversible by reverse mtg, additional ratings, 39 cfm w/2400 rpm at 50 hz, 52 cfm w/3100 rpm at 60 hz, class h insulation motor windings

Frequency In Hertz:

50.0 and 60.0 and 400.0

Material:

Aluminum

Unpackaged Unit Weight:

1.000 pounds

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0