

View Online at <https://aerobasegroup.com/nsn/4140-00-701-0309>

**Speed Adjustments:**

Single speed

**Length:**

1.734 inches

**Flow Direction:**

Inward

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3350.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.2 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

57.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.038 horsepower

**Housing Inside Diameter:**

3.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

W/rim at ea end of venturi tube for clamp mtg, air flow reversible by reverse mtg, additional ratings, 39 cfm w/2400 rpm at 50 hz, 52 cfm w/3100 rpm at 60 hz, class h insulation motor windings

**Frequency In Hertz:**

50.0 and 60.0 and 400.0

**Material:**

Aluminum

**Unpackaged Unit Weight:**

1.000 pounds

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0