

View Online at <https://aerobasegroup.com/nsn/4140-00-723-4107>

**Width:**

Between 10.000 inches and 10.312 inches

**Length:**

5.000 inches

**Environmental Protection:**

Humidity proof and fungus proof

**Ambient Temperature At Full Rated Power:**

-40.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5300.0

**Electrical Connection Type:**

Terminal

**Outlet Inside Width:**

2.625 inches

**Outlet Inside Height:**

2.000 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

220.000 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

416.0 ac

**Prime Mover Power Rating:**

0.083 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Height:**

5.968 inches

**Material:**

Steel

**Quantity:**

2

**Surface Treatment:**

Enamel housing outside

**Style Designator:**

Fixed, dual impeller, rectangular outlet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0