## NSN 4140-00-725-7013

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-725-7013 Stage Quantity: **Speed Adjustments:** Single speed Flow Direction: Outward **Ambient Tempurature At Full Rated Power:** 50.0 degrees celsius **Operating Speed At Rated Capacity In Rpm:** 3500.0 **Electrical Connection Type:** Terminal **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Rotation Direction For Which Designed:** Counterclockwise **Features Provided:** Safety impeller guard **Voltage In Volts And Current Type:** 440.0 ac **Prime Mover Power Rating:** 0.333 horsepower **Housing Inside Diameter:** 7.500 inches **Prime Mover Drive Shaft Bearing Type:** Ball Phase: Single Frequency In Hertz: 60.0 Material: Aluminum alloy housing **Material Specification:** Qq-a-601, class 3m, t6 federal specification single material response housing **Surface Treatment:** Zinc housing outside

**Style Designator:** Fixed

## NSN 4140-00-725-7013

Vaneaxial Fan - Page 2 of 2



Reference	Number	Differentiating	<b>Characteristics:</b>
11010101100	HUIIDEI	Differentiation	Ullai actel istics.

As differentiated by size 1075ab46s2

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A087a0