

View Online at <https://aerobasegroup.com/nsn/4140-00-726-2406>

**Stage Quantity:**

1

**Speed Adjustments:**

Two speed

**Width:**

36.125 inches

**Length:**

35.938 inches

**Environmental Protection:**

Splash proof

**Ambient Temperature At Full Rated Power:**

65.0 degrees celsius

**Outlet Inside Width:**

12.875 inches

**Outlet Inside Height:**

21.500 inches

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

4000.0 cubic feet per minute

**Outlet Location:**

Top

**Prime Mover Power Rating:**

4.000 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Height:**

44.875 inches

**Material:**

Steel

**Quantity:**

1

**Surface Treatment:**

Anodize blade or zinc blade

**Style Designator:**

Fixed, rectangular outlets

**Test Data Document:**

81349-milf19004 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Or Standard:**

C type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0