

View Online at <https://aerobasegroup.com/nsn/4140-00-729-6191>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

6.406 inches

Length:

6.062 inches

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3350.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

1.094 inches

Outlet Inside Height:

2.406 inches

Static Pressure At Specificationified Air Flow Rate:

0.8 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

48.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.057 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Single

Height:

4.469 inches

Material:

Steel

Quantity:

1

Surface Treatment:

Enamel housing outside

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0