

View Online at <https://aerobasegroup.com/nsn/4140-00-766-6045>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

1.870 inches

Length:

1.469 inches

Flow Direction:

Inward

Environmental Protection:

Humidity proof and salt spray resistant and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

16500.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

3 threaded insert and 3 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

46.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.032 horsepower

Housing Inside Diameter:

1.990 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Quantity:

1

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0