

View Online at <https://aerobasegroup.com/nsn/4140-00-772-5244>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

6.750 inches

**Flow Direction:**

Inward

**Ambient Temperature At Full Rated Power:**

-65.0 degrees celsius and 120.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

11275.0

**Electrical Connection Type:**

Terminal and wire lead

**Static Pressure At Specificationified Air Flow Rate:**

8.3 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

300.0 cubic feet per minute

**Voltage In Volts And Current Type:**

416.0 ac

**Prime Mover Power Rating:**

0.700 horsepower

**Housing Inside Diameter:**

5.500 inches

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Quantity:**

1

**Surface Treatment:**

Anodize and zinc

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification 1st treatment response or mil-p-8585 military specification 2nd treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.