

View Online at <https://aerobasegroup.com/nsn/4140-00-782-7688>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Corrosion resistant and fungus resistant and moisture resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

9700.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 rim and 3 lug

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

26.0 cubic feet per minute

**Voltage In Volts And Current Type:**

90.0 ac or 120.0 ac

**Prime Mover Power Rating:**

0.024 horsepower

**Housing Inside Diameter:**

Between 1.980 inches and 2.000 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

1380.0 and 1835.0

**Material:**

Aluminum

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-5557 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.