

View Online at <https://aerobasegroup.com/nsn/4140-00-782-7688>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Inward

Environmental Protection:

Corrosion resistant and fungus resistant and moisture resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

9700.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 rim and 3 lug

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Nonsparking

Air Flow Rate:

26.0 cubic feet per minute

Voltage In Volts And Current Type:

90.0 ac or 120.0 ac

Prime Mover Power Rating:

0.024 horsepower

Housing Inside Diameter:

Between 1.980 inches and 2.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

1380.0 and 1835.0

Material:

Aluminum

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-5557 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.