

View Online at <https://aerobasegroup.com/nsn/4140-00-789-6935>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

4.500 inches

Operating Speed At Rated Capacity In Rpm:

22900.0

Electrical Connection Type:

Connector receptacle

Static Pressure At Specificationified Air Flow Rate:

40.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

6 unthreaded hole

Features Provided:

Radio interference shielding

Air Flow Rate:

300.0 cubic feet per minute

Outlet Location:

Center

Voltage In Volts And Current Type:

208.0 ac

Prime Mover Power Rating:

3.000 horsepower

Discharge Direction:

Horizontal

Phase:

Three

Special Features:

Impeller rotation direction: counterclockwise; fan style: f10a fixed, inverted, round outlet; fan length: 9.812 in. Nom.; fan width: 7.125 in. Nom.; fan height: 7.937 in. Nom.; fan qty: 1; operating control type: any acceptable; bearing type: any acceptable

Frequency In Hertz:

400.0

Material:

Steel housing

Surface Treatment:

Zinc housing outside

Test Data Document:

01359-201486 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0