

View Online at <https://aerobasegroup.com/nsn/4140-00-789-6935>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

4.500 inches

**Operating Speed At Rated Capacity In Rpm:**

22900.0

**Electrical Connection Type:**

Connector receptacle

**Static Pressure At Specificationified Air Flow Rate:**

40.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Features Provided:**

Radio interference shielding

**Air Flow Rate:**

300.0 cubic feet per minute

**Outlet Location:**

Center

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Power Rating:**

3.000 horsepower

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Special Features:**

Impeller rotation direction: counterclockwise; fan style: f10a fixed, inverted, round outlet; fan length: 9.812 in. Nom.; fan width: 7.125 in. Nom.; fan height: 7.937 in. Nom.; fan qty: 1; operating control type: any acceptable; bearing type: any acceptable

**Frequency In Hertz:**

400.0

**Material:**

Steel housing

**Surface Treatment:**

Zinc housing outside

**Test Data Document:**

01359-201486 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0