

View Online at <https://aerobasegroup.com/nsn/4140-00-792-0873>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

1.600 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Humidity proof and moisture resistant and salt spray resistant and shock proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

22000.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 clamp

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

21.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

16.0 watts

**Housing Inside Diameter:**

1.562 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-5557, type 4 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.