

View Online at <https://aerobasegroup.com/nsn/4140-00-793-5180>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

6.906 inches

Length:

8.844 inches

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

Not rated

Operating Speed At Rated Capacity In Rpm:

3000.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

3.000 inches

Outlet Inside Height:

3.188 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

248.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.235 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Three

Height:

7.812 inches

Material:

Steel

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0