

View Online at <https://aerobasegroup.com/nsn/4140-00-793-5180>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

6.906 inches

**Length:**

8.844 inches

**Environmental Protection:**

Humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

Not rated

**Operating Speed At Rated Capacity In Rpm:**

3000.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

3.000 inches

**Outlet Inside Height:**

3.188 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

248.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.235 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Three

**Height:**

7.812 inches

**Material:**

Steel

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0