

View Online at <https://aerobasegroup.com/nsn/4140-00-802-1963>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

3.340 inches

Length:

2.680 inches

Ambient Temperature At Full Rated Power:

Not rated

Operating Speed At Rated Capacity In Rpm:

9000.0

Electrical Connection Type:

Terminal block

Outlet Inside Width:

1.250 inches

Outlet Inside Height:

1.375 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 3 threaded insert

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

28.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.022 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Blade Shape:

Forward curve

Phase:

Single

Special Features:

Positioning when mtg determines discharge blast direction, class a insulation motor windings

Height:

3.050 inches

Material:

Steel blade

Surface Treatment:

Zinc blade

Style Designator:

Fixed, rectangular outlets

Fsc Application Data:

Power supply, test set, radar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0