

View Online at <https://aerobasegroup.com/nsn/4140-00-810-1973>

Speed Adjustments:

Single speed

Length:

10.440 inches

Flow Direction:

Outward

Environmental Protection:

Fungus resistant and humidity proof and vibration proof

Ambient Temperature At Full Rated Power:

40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Operating Speed At Rated Capacity In Rpm:

5850.0

Electrical Connection Type:

Connector receptacle

Static Pressure At Specificationified Air Flow Rate:

2.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Thermal protective device

Air Flow Rate:

4300.000 cubic feet per minute

Voltage In Volts And Current Type:

208.0 ac or 416.0 ac

Prime Mover Power Rating:

3.820 horsepower

Housing Inside Diameter:

15.750 inches

Phase:

Three

Special Features:

Automatic reset

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Chromate zinc and enamel

Surface Treatment Specification:

Mil-p-8585 military specification 1st treatment response and tt-e-527, black federal specification 2nd treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-p-8585 spec.