

View Online at <https://aerobasegroup.com/nsn/4140-00-810-9330>

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Outward

Environmental Protection:

Fungus resistant and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-18.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

10500.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 ring

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Nonsparking

Air Flow Rate:

30.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.016 horsepower

Housing Inside Diameter:

1.990 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Anodize housing outside

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0