

View Online at <https://aerobasegroup.com/nsn/4140-00-812-5224>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

1.470 inches

Flow Direction:

Outward

Environmental Protection:

Moisture resistant

Ambient Temperature At Full Rated Power:

100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

17000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

3 lug and 3 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

48.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

18.0 watts

Housing Inside Diameter:

1.891 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response

Style Designator:

Fixed

Test Data Document:

06424-2653569-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.