

View Online at <https://aerobasegroup.com/nsn/4140-00-816-0603>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

4.880 inches

Length:

3.760 inches

Environmental Protection:

Fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-29.0 degrees celsius and 52.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3350.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

1.281 inches

Outlet Inside Height:

1.375 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 3 threaded insert

Rotation Direction For Which Designed:

Clockwise and counterclockwise

Features Provided:

Nonsparking

Air Flow Rate:

20.0 cubic feet per minute

Outlet Location:

Bottom and top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.003 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical down and vertical up

Phase:

Single

Height:

2.880 inches

Material:

Stainless steel blade

Surface Treatment:

Anodize housing outside

Style Designator:

Fixed, dual impeller, rectangular outlet

Test Data Document:

02734-8703534 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0