

View Online at <https://aerobasegroup.com/nsn/4140-00-816-0603>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

4.880 inches

**Length:**

3.760 inches

**Environmental Protection:**

Fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-29.0 degrees celsius and 52.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3350.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

1.281 inches

**Outlet Inside Height:**

1.375 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 3 threaded insert

**Rotation Direction For Which Designed:**

Clockwise and counterclockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

20.0 cubic feet per minute

**Outlet Location:**

Bottom and top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.003 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical down and vertical up

**Phase:**

Single

**Height:**

2.880 inches

**Material:**

Stainless steel blade

**Surface Treatment:**

Anodize housing outside

**Style Designator:**

Fixed, dual impeller, rectangular outlet

**Test Data Document:**

02734-8703534 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0